

Monitor XL™

4 Zone LCD Suite Module



OVERVIEW

The Monitor XL 4-zone LCD Suite Module provides an integrated security solution ideal for the condominium suite owner. Each module is a fully self-contained alarm panel that connects to the base building Monitor XL system for configuration and reporting. A single platform provides individual suite security, base building access, underground parking access, wireless and hardwired panic alarms, access to restricted amenities, video surveillance and elevator control to each floor.

Up to eight residents can be configured per suite with four preconfigured authorities. Users may change their unique PIN at any time. Those with Master Authority can edit and delete the authority and PIN of other residents within the suite.

The LCD keypad supports four suite alarm zones and three programmable personal safety alerts, such as fire, police and medical. The keypad modules allow for remote arming, disarming and silencing of alarms. Each function is programmable by individual suite. An Activity Monitoring feature monitors movement within the suite while the suite is disarmed.

Users can log on to the keypad with a personal PIN or a building-access G-Prox II token. For higher security, the system can be set up to require both the token and a personal PIN to disarm the suite, but only the token to arm the suite.

STANDARD FEATURES

- Fully self-contained alarm panel
- Connects to the base building Monitor XL system
- Supports up to eight individual users
- Four suite alarm zones and three programmable personal safety alerts
- Remote arming, disarming and silencing of alarms
- Activity Monitoring feature
- Built-in G-Prox II reader

Monitor XL™

4 Zone LCD Suite Module

North America
T 855-286-8889

Asia
T 852-2907-8108

Australia
T 61-3-9239-1200

Europe
T 32-2-725-11-20

Latin America
T 561-998-6114

Specifications

Description

Inputs	4 fully programmable inputs
Anti-tamper device	Integrated
Outputs	1 Low Current (10mA)
Point types	16 pre-defined, 20 custom
Supervision	Normally Closed
	Normally Open with End-of-Line
	Normally Closed with End-of-Line
	Form 'C' with End-of-Line
	Dual End-of-Line
	Custom End-of-line value
System architecture	RS485 communications from Module to Monitor XL main panel.
Power requirements	12 volts DC, 95mA per Module
Recommended Cable Requirements	1 twisted pair #22 stranded with overall shield
Dimensions (WxHxD)	5.25 x 4.75 x 1 in. (132 x 118 x 25mm)
Material	Molded Plastic, White
Compatibility	Monitor ISM or XL panel version V4.58f firmware and Director Enterprise and Enterprise Elite version software.
Environmental	Each Monitor XL panel can be connected directly to an IP-based network with the optional IP connectivity interface
Temperature Range	0° C to 50° C, (32° F- 120°F)

Ordering Information

120-8014	4 Zone LCD Suite Module, White
----------	--------------------------------



interlogix.com/verex

Specifications subject to change without notice.

© 2012 Interlogix.
All rights reserved.
206-3526 2012/06 (69399)