





SafeStore Auto Maxi

Self-service safe deposit boxes

SafeStore Auto Maxi is a fully automated system of safe deposit boxes housed in a high-security vault. Customers are able to access this compact and flexible solution 24-hours a day through a secure room, which may or may not be located on the same level as the vault itself. SafeStore Auto Maxi allows you to offer the most user-


friendly and convenient service possible, while giving your staff the freedom to perform more value added activities such as upselling or winning new customers. The accessibility and convenience of SafeStore Auto Maxi offers a high tech, competitive advantage for financial institutions looking to update their solution offering.





Design and production: Gunnebo. Photos Credis: Gunnebo. The data given in this material may be subject to change without further notice. The Gunnebo logos and "Gunnebo – For a safer world" are registered trademarks of Gunnebo AB.

SafeStore Auto Maxi

Self-service safe deposit boxes







Concept

SafeStore Auto Maxi delivers a unique and memorable customer experience by automating the process of accessing, storing, and securing valuables within innovative financial institutions. Customers first enter a secure room, which may or may not be located on the same level as the vault. This gives a financial institution the flexibility to install the boxes in the basement and place the secure room in the bank lobby freeing up physical space for sales activities. In addition to the safe deposit box application, SafeStore Auto Maxi can function as a transfer safe and deposit system for valuables. The intelligent transportation system guarantees limited wait time for the customer. Thanks to the system's advanced technology, next-level biometric security features, and 24-hour availability, SafeStore Auto Maxi provides return on investment far sooner than manual, outdated safety deposit box alternatives.

Features

One of the best aspects of the SafeStore Auto Maxi system is its versatility in configuration and ease of on-site assembly allowing the financial institution to meet the unique needs of their specific customer base. Mixing and matching the five various box sizes allow you a one-of-a-kind unit, fitting your specific space requirements. The box delivery point can also be customized by locating it either in the basement or the lobby, or even by incorporating one in each location. Thanks to horizontal and vertical mechanisms working simultaneously, customers experience a short wait time regardless of where the delivery point is placed. Users enter the secure room using either a card or biometric fingerprint reader, and then navigate through a simple touch screen guide to access their valuables. From an administration perspective, the SafeStore Auto Maxi can interface with our SafeControl monitoring software, hosted either centrally or locally. Additional security options include implementation of security PINs, cards, physical keys, biometrics, video surveillance, and a high-security electronic lock for the vault. For smaller installations the SafeStore Auto Mini or SafeStore Auto Midi is available.

Design

SafeStore Auto Maxi has a modern, compact design allowing ample savings in physical space. As an innovative and flexible solution, the cassettes are dispensed at an ergonomic, user-friendly height either from the front of the machine or from above.

Product Data

Connections: 110V-120V (AC)/50-60Hz, Active current: 4.0A (max.), Line fused: 20A

Security level: The system is built in a UL listed class 1, 2 or 3 vault

HOW IT WORKS

- 1. The customer passes a layer of security using a card or biometrics and is granted access to a secure room
- 2. The customer logs into the system using a bank card, PIN, and/or fingerprints
- **3.** The system automatically and quickly delivers the customer's unit
- **4.** The customer uses his or her personal key to access the contents
- 5. Once finished, the unit is quickly returned to its secure location within the vault

BOX DATA (in.)

Max load 55 lbs./box

Outer height	Inne H	r dimen D	sions W
2.7	1.9	12.8	9.3
4.1	3.3	12.8	9.3
5.4	4.6	12.8	9.3
6.7	6.0	12.8	9.3
8.1	7.3	12.8	9.3

